

CHEMICAL SCOPE			Tick - Yes (✓) as applicable
	ROUND 1- Basic Tests		
Scheme - PT/TEX/ ROUND-1 /CHEM/ 2020 (to be conducted in January - April 2020)	Colour fastness to Rubbing Range: Grade 1 to 5	ISO 105 X12	<input type="checkbox"/>
	Colour fastness to domestic and commercial laundering Range: Grade 1 to 5	ISO 105 C06 (A2S, 40°C)	<input type="checkbox"/>
	Colour fastness to water Range: Grade 1 to 5	ISO 105 E01	<input type="checkbox"/>
	Colour fastness to dry clean Range: Grade 1 to 5	ISO 105 D01	<input type="checkbox"/>
	Determination of pH of aqueous extract Range: 1 to 14	ISO 3071	<input type="checkbox"/>
	ROUND 1- Special Tests		
	Colourfastness to ozone Range: Grade 1 to 5	ISO 105 G03	<input type="checkbox"/>
	Colourfastness to Burnt Gas Fume Range: Grade 1 to 5	ISO 105 G02	<input type="checkbox"/>
	Fibre Content Range: 0.1 - 100%	ISO 1833	<input type="checkbox"/>
	ROUND 2- Basic Tests		
Scheme - PT/TEX/ ROUND-2 /CHEM/ 2020 (to be conducted in August – November 2020)	Colourfastness to Crocking: Crock meter Method Range: Grade 1 to 5	AATCC 8	<input type="checkbox"/>
	Colourfastness to Laundering, Home & Commercial: Accelerated Range: Grade 1 to 5	AATCC 61 (2A, 49°C)	<input type="checkbox"/>
	Colourfastness to Water Range: Grade 1 to 5	AATCC 107	<input type="checkbox"/>
	Colourfastness to Dry clean Range: Grade 1 to 5	AATCC 132	<input type="checkbox"/>
	pH of the Water-Extract from Wet Processed Textiles Range: 1 to 14	AATCC 81	<input type="checkbox"/>
	ROUND 2- Special Tests		
	Colourfastness to ozone Range: Grade 1 to 5	AATCC 109	<input type="checkbox"/>
	Colourfastness to Burnt Gas Fume Range: Grade 1 to 5	AATCC 23	<input type="checkbox"/>
	Fibre Identification: Quantitative Range: 0.1 to 100%	AATCC 20 / AATCC 20A	<input type="checkbox"/>

MECHANICAL SCOPE			Tick - Yes (√) as applicable	
ROUND 1- Basic Tests				
Scheme - PT/TEX/ ROUND-1 /MECH/ 2020 (to be conducted in January - April 2020)	End (Warp) and Pick (Filling) Count of Woven Range: End/Picks per 10 centimetre: Range: 30 - 400 ends/picks per 10 centimetre	ISO 7211-2	<input type="checkbox"/>	
	Mass Per Unit Area (Weight) of Fabric Range: 30 - 400 GSM	ISO 3801	<input type="checkbox"/>	
	Breaking Load – Strip Range: 20 - 800 N	ISO 13934-1	<input type="checkbox"/>	
	Tear Strength of Fabric (Elmendorf) Range: 2 - 70 N	ISO 13937-1	<input type="checkbox"/>	
	ROUND 1- Special Tests			
	Yarn Count Range: 10 - 80 Ne (English Count)	ISO 7211-5	<input type="checkbox"/>	
	Stretch & Recovery (Strip - Woven) Range: 1 - 100%	ISO 14704 - 1	<input type="checkbox"/>	
Trouser Shaped Tear (Single Tear) Range: 3 - 300 N	ISO 13937-2	<input type="checkbox"/>		
ROUND 2- Basic Tests				
Scheme - PT/TEX/ ROUND-2 /MECH/ 2020 (to be conducted in August – November 2020)	End (Warp) and Pick (Filling) Count of Woven Fabrics Range: 30 - 400 ends/picks per inch	ASTM D3775	<input type="checkbox"/>	
	Mass Per Unit Area (Weight) of Fabric Range: 1.4 - 10 oz/yd ²	ASTM D3776	<input type="checkbox"/>	
	Breaking Strength - Strip Method Range: 4 - 180 lb	ASTM D5035	<input type="checkbox"/>	
	Tear Strength of Fabric Range: 0.4 - 20 lb	ASTM D1424	<input type="checkbox"/>	
	ROUND 2- Special Tests			
	Yarn Count Range: 10 - 80 Ne (English Count)	ASTM D1059	<input type="checkbox"/>	
	Stretch & Recovery (Woven) Range: 1 - 100 %	ASTM D3107	<input type="checkbox"/>	
Tongue Tear (Single Rip) Range: 0.5 - 70 lb	ASTM D2261	<input type="checkbox"/>		



BUREAU VERITAS PTP DIVISION PT SCHEDULE 2020



For any kind of Query Kindly Contact--

For General Queries-

Mrs.Preeti Mehta(+91-9667400643<preeti.mehta@bureauveritas.com>)

Mr. Nikhil Sharma(+92-9205690660<nikhil.sharma@bureauveritas.com>)

Mr.Gaurav Davesar(+91-8448203900<Gaurav.Davesar@bureauveritas.com>)

For Technical Queries-

Dr. Puneet Bhardwaj(+91- 8130866558<puneet.bhardwaj@bureauveritas.com>)

Mr. Kamal Talukadar(+91-9205 281 971<kamal.talukdar@bureauveritas.com>)